






## **ButtKicker/Pearl Product Comparison Chart for Pro Audio and MI**

		<b>For Drummers &amp; other Seated Musicians or Studio Engineers</b>			<b>Bass Players &amp; other Standing Musicians</b>	
						
<b>PRODUCT</b>		<b>ButtKicker Drum Throne Rig</b>	<b>Pearl Throne Thumper by ButtKicker</b>	<b>ButtKicker Gamer</b>	<b>ButtKicker Standing Platform Kit</b>	<b>Large Platform and Stage Installations</b>
<b>IDEAL FOR</b>		Thrones and other seats – Heavy duty	Thrones and single-post seats – Medium duty	Thrones and single-post seats – Light duty	Bass players and other standing musicians	Large platforms/stages and multiple units
<b>Transducer Specifications</b>	<b>TRANSDUCER TYPE</b>	ButtKicker Concert	ButtKicker Advance Series	ButtKicker mini Series	ButtKicker Concert	ButtKicker LFE (multiple units as needed)
	<b>INTERNAL PISTON MASS</b>	3.25 lbs.	1 lbs.	6 oz.	3.25 lbs.	3.25 lbs.
	<b>DIMENSIONS</b>	5.375" H x 5.375" W	4.375" H	11.5" L x 2.75" H x 3" W	5.375" H x 5.375" W	5.5"
	<b>FREQUENCY RESPONSE</b>	5 – 200 Hz	10 - 250 Hz	10 – 250 Hz	5 – 200 Hz	5 – 200 Hz
	<b>TOTAL WEIGHT</b>	11 lbs. / 5 kgs.	Approx. 5 lbs.	3 lbs. / 1.3 kgs.	11 lbs. / 5 kgs.	11 lbs. / 5 kgs.
	<b>NOMINAL IMPEDANCE</b>	2 ohms	4 ohms	2 ohms	2 ohms	4 ohms
	<b>POWER HANDLING</b>	400 watts min. / 1500 watts max.	75 watt min. / 400 wats max.	75 watt min. / 400 watt max.	400 watts min. / 1500 watts max.	400 watts min. / 1500 watts max.
	<b>MOUNTING OPTIONS</b>	Screw or DTM Mounting Plate	Easy-Clamp™	Easy-Clamp™	Screw/Bolt	Screw/Bolt

PAGE 1

Continued on page 2...

... Continued from page 1

<b>PRODUCT</b>	<b>ButtKicker Drum Throne Rig</b>	<b>Pearl Throne Thumper by ButtKicker</b>	<b>ButtKicker Gamer</b>	<b>ButtKicker Standing Platform Kit</b>	<b>Large Platform and Stage Installations</b>	
<b>Amplifier Specifications</b>	<b>AMPLIFIER WATTAGE</b>	1900 Watts @ 2 ohms 1000 Watts @ 4 ohms	200 Watts @ 4 ohms (2 ohms Not Recommended)	90 Watts @ 2 ohms 45 Watts @ 4 ohms	1900 Watts @ 2 ohms 1000 Watts @ 4 ohms	1900 Watts @ 2 ohms 1000 Watts @ 4 ohms
	<b>HIGH FILTER CUTOFF</b>	Variable, 40 – 160 Hz	N/A	Variable, 40 – 160 Hz	Variable, 40 – 160 Hz	Variable, 40 – 160 Hz
	<b>LOW FILTER CUTOFF</b>	25 Hz (switchable)	N/A	25 Hz (switchable)	25 Hz (switchable)	25 Hz (switchable)
	<b>INPUT</b>	RCA and 1/4" inputs with 160 mVolt and 1.25 Volt sensitivities	1/4" input with 100 mVolt Sensitivity	RCA input with 75 mVolt sensitivity	RCA and 1/4" inputs with 160 mVolt and 1.25 Volt sensitivities	RCA and 1/4" inputs with 160 mVolt and 1.25 Volt sensitivities
	<b>OUTPUT</b>	5-way Binding Post	5-way Binding Post	5-way Binding Post	5-way Binding Post	5-way Binding Post
	<b>POWER COMPATIBILITY</b>	Either 120v or 240v versions. NOT SWITCHABLE	Either 120v or 240v versions. NOT SWITCHABLE	Either 120v or 240v versions. NOT SWITCHABLE	Either 120v or 240v versions. NOT SWITCHABLE	Either 120v or 240v versions. NOT SWITCHABLE
	<b>COOLING</b>	Convection Cooled	Convection Cooled	Convection Cooled	Convection Cooled	Convection Cooled
<b>MSRP</b>	\$669.99	\$499.99	\$149.95	\$649.85	Varies by product configuration	
<b>MAP</b>	\$539.99	\$299.99	\$129.99	\$529.99	Varies by product configuration	
<b>AVAILABLE THROUGH</b>	Guitammer	Pearl	Guitammer	Guitammer	Guitammer	